



NOFI BUSTER



Inventory

	Great Lakes	Quebec	Atlantic	Total
HARBOUR BUSTER 600	1	-	-	1
CURRENT BUSTER 600	-	1	-	1
OCEAN BUSTER 1000	-	1	-	1
Total	1	2		3

Application

The NOFI Harbour/Current/Ocean Busters are unique products for containing and recovering oil, with increased skimming efficiency due to low oil-layer turbulence in the separator at the end of the system. They can be operated in sheltered as well as unsheltered water. They are capable of containing and collecting oil at towing speeds up to 3.0 – 4 knots. These units can be deployed from a dock, a floating platform or the deck of a service tug. Two vessels are required to tow a unit. The NOFI Current Buster is also expected to be well suited for fast running rivers and in narrow, high current straits.

Description

The NOFI Buster consists of a Front Sweep guiding or herding oil into the combined Collector/Skimming device and then into the Separator Tank from where the oil is recovered by a simple pump or a conventional skimmer. In addition to containing oil in high towing speeds (and/or currents), it also separates the oil from the water and positively “controls” the oil for uncomplicated and highly efficient oil recovery – replacing the need for conventional skimmers (by applying pumps instead).

Operating data

Advancing rate: 3.0 – 4 knots max.

Ancillaries

Diesel hydraulic power unit
Gas powered boom inflators

Technical data

	<u>HARBOUR BUSTER - 600</u>	<u>CURRENT BUSTER - 600</u>	<u>OCEAN BUSTER - 1000</u>
Boom overall height:	1.2 m (4 ft 0 in)	1.2 m (4 ft 0 in)	1.4 m (4 ft 7 in)
Boom draught:	0.6 m (2 ft 0 in)	0.6 m (2 ft 0 in)	1.4 m (4 ft 7 in)
Boom freeboard:	0.6 m (2 ft 0 in) 1.4 m (during operation)	0.6 m (2 ft 0 in) 2 m (during operation)	1 m (3 ft 3 in)
Depth of separator:			6 m (during operation)
Swath width:	15 m	20 m	50 m
Separator volume:	5 cu. m. (before loss of oil) 15 cu. m. (gross volume)	10 cu. m. (before loss of oil) 25 cu. m. (gross volume)	30 cu. m. (before loss of oil) 70 cu. m. (gross volume)

Eastern Canada Response Corporation Ltd.
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613)-230-7369 Fax (613)-230-7344