



ELASTEC SKIMMER



Inventory

	Great Lakes	Québec	Atlantic	Total
Elastec TDS-136	1	3	2	6
Elastec TDS-118G	1	2	-	3
Total	2	5	2	9

Application

Suitable for the recovery of light to high viscosity oil, but most useful in heavy oil recovery. Suitable for shoreline and sheltered water usage. Can be deployed from shoreline, vessel or recovery barge.

Description

An oleophilic drum skimmer, built of aluminium frame and moulded polyethylene drums. The oil is picked off the water by the rotating drum and scraped off into a sump. The 188G features a grooved drum providing improved recovery rate. An integrated or external pump moves the recovered oil to an external storage unit.

Operating Data

Nominal recovery rate:	<u>118</u> 8 tons/hr	<u>136</u> 15 tons/hr
De-rated recovery rate:	38 tons/day	72 tons/day

Ancillaries

Power pack
118 – External pump
136 – Onboard submersible pump (2 in)

Technical Data

Length:	<u>118</u> 0.9 m	<u>136</u> 0.9 m (3 ft 0 in)
Width:	1.2 m	2.3 m (7 ft 8 in)
Height:	0.4 m	0.4 m (1 ft 3 in)
Weight:	27 kg	68 kg (150 lbs)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc.ca