



RIGID HULL INFLATABLES



Inventory

	Great Lakes	Québec	Atlantic	Total
Hurricane 590	-	-	2	2
Zodiac Mark IV	-	-	2	2
Sillinger 425UM	-	6	-	6
Sillinger 525UM	-	4	2	6
Sillinger 570UM	1	3	-	4
Total	1	13	6	20

Application

Inflatable boats provide versatility in response operations for both transportation and active duty in sheltered water operations.

Description

Rigid hull inflatable boats equipped with outboard motor (15 to 70 HP); molded fibreglass, plastic or metal hulls (including floor) with a fabric air filled flotation collar that makes up the bow and sides of the boat. The rigid hull provides stability for operation of the boat in most sea conditions. The flotation collar supplies buoyancy (with reserve), stability and absorbs wave energy to soften the ride in rough conditions.

Operating Data

Speed: up to 30 knots

Ancillaries

VHF
Some equipped with radar

Technical Data

	<u>Hurricane</u>	<u>Zodiac Mark IV</u>	<u>Sillinger 425UM</u>	<u>Sillinger 535UM</u>	<u>Sillinger 570UM</u>
Length:	5.9 m (21 ft)	5.3 m (17 ft 5 in)	4.3 m (14 ft)	5.3 m (18 ft)	5.7 m (19 ft)
Width:	1.7 m (5 ft 6 in)	2.1 m (7 ft)	1.8 m (6 ft)	2.2 m (7 ft)	2.2 m (7 ft 5 in)
Draft:	40 cm (16 in)	40 cm (16 in)	30 cm (12 in)	35 cm (14 in)	40 cm (16 in)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc.ca