



SMALL BOATS 12 – 18 FT



Inventory

| | Great Lakes | Québec | Atlantic | Total |
|---------------------|-------------|-----------|-----------|-----------|
| Small Boat 12' Alum | - | 9 | - | 9 |
| Small Boat 14' Alum | - | 4 | 6 | 8 |
| Small Boat 16' Punt | 1 | - | - | 1 |
| Small Boat 16' Alum | 1 | - | 5 | 3 |
| Small Boat 18' Alum | 1 | - | - | 1 |
| Total | 3 | 13 | 11 | 22 |

Application

These boats are primarily used for spill observation, transporting equipment, small material and personnel, for tending shoreline skinning and for shoreline treatment operations.

Description

For stability purposes these boats are typically flat bottom with slanted square bow, unsinkable filled with polyfoam at bow and under the seat.

Operating Data

Speed: up to 10 knots
Outboard motor: 9.9 to 40 HP

Ancillaries

Rope and anchor
Paddle

Technical Data

Length: From 3.6 m to 5.5 m (12 to 18 ft)
Beam: From 1.5 m to 2.2 m (5 to 7 ft)
Draft: From 0.2 to 0.5 m (8 to 20 in)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc.ca