



SOLID FLOTATION BOOM



Inventory (meters)

	Great Lakes	Québec	Atlantic	Total
GP 20 in.	7,970	730	4,008	12,708
GP 24 in.	-	20,032	7,231	27,263
GP 36 in.	-	2,000	5,179	5,710
Total	7,970	22,762	16,418	47,150

Application

Oil containment boom suitable for shoreline and sheltered water. It is stored in trailers, containers and on deck of seatrucks and pontoons.

Description

It is a general purpose boom with a solid flotation core and made of polyurethane-coated polyester fabric.

Operating Data

Maximum current: 1.5 knots

Ancillaries

Rope
Anchors
Buoys

Technical Data

	<u>20 in.</u>	<u>24 in.</u>	<u>36 in.</u>
Boom section:	15 m (50 ft)	15 m (50 ft)	15 m (50 ft)
Boom overall height:	51 cm (20 in)	61 cm (24 in)	91 cm (36 in)
Boom freeboard:	15 cm (6 in)	20 cm (8 in)	30 cm (12 in)
Boom draft:	36 cm (14 in)	41 cm (16 in)	61 cm (24 in)

ECRC~SIMEC
Suite 1201, 275 Slater Street, Ottawa K1P 5H9
Phone (613) 230-7369 Fax (613) 230-7344
Web: www.ecrc.ca