



# SOLID FLOTATION BOOM



## Inventory (meters)

	Great Lakes	Québec	Atlantic	Total
GP 20 in.	7,970	730	4,008	12,708
GP 24 in.	-	20,032	7,231	27,263
GP 36 in.	-	2,000	5,179	5,710
<b>Total</b>	<b>7,970</b>	<b>22,762</b>	<b>16,418</b>	<b>47,150</b>

## Application

Oil containment boom suitable for shoreline and sheltered water. It is stored in trailers, containers and on deck of seatrucks and pontoons.

## Description

It is a general purpose boom with a solid flotation core and made of polyurethane-coated polyester fabric.

## Operating Data

Maximum current: 1.5 knots

## Ancillaries

Rope  
Anchors  
Buoys

## Technical Data

	<u>20 in.</u>	<u>24 in.</u>	<u>36 in.</u>
Boom section:	15 m (50 ft)	15 m (50 ft)	15 m (50 ft)
Boom overall height:	51 cm (20 in)	61 cm (24 in)	91 cm (36 in)
Boom freeboard:	15 cm (6 in)	20 cm (8 in)	30 cm (12 in)
Boom draft:	36 cm (14 in)	41 cm (16 in)	61 cm (24 in)

ECRC~SIMEC

Suite 1201, 275 Slater Street, Ottawa K1P 5H9

Phone (613) 230-7369 Fax (613) 230-7344

Web: [www.ecrc.ca](http://www.ecrc.ca)